







FASTENERS & PLATES






SYSTEM ACCESSORIES

Versico offers a wide variety of fasteners and plates to enhance our roofing systems. From pre-assembled choices for VersiGard® installations to Purlin fasteners for Metal Retrofit Systems and HPVX plates for VersiWeld® options, our focus is to provide all components necessary for the application of a long-lasting, single-ply roofing system from Versico.






| PRODUCT | DECK TYPE | USAGE | DESCRIPTION | SIZE | PACKAGING | |
|---|--|---|---|--|--------------------------------|--------------------|
| | | | | | SIZE | # PER CTN |
|  <p>HPV Fastener</p> | Steel (22 gauge & heavier) Wood Decks | VersiGard Membrane and Insulation Securement | <ul style="list-style-type: none"> • #3 Square Drive Recess • Flat Wafer Style Head and Buttfress Threads • Mini Drill Point | <ul style="list-style-type: none"> • 1¼"– 4¼" (½" Increments) • 5"– 15" (1" Increments) • <i>Longer Fastener Sizes Available As Special Order</i> | 1¼"– 6" 7"– 12" 13"– 15" | 1000 500 250 |
|  <p>InsulTite</p> | Wood Decks Steel (22 gauge & heavier) | Insulation Only | <ul style="list-style-type: none"> • #3 Phillips Head • Deep Buttfress Threads | <ul style="list-style-type: none"> • 1½", 2¼", 2⅞", • 3¼", 3¾", 4½" • 5"– 8" (1" Increments) | 1½"– 8" | 1000 |
|  <p>K-Fast (Sure-Tite)</p> | Steel (22 gauge & heavier) | VersiGard Membrane Securement For Mechanically Attached Systems | <ul style="list-style-type: none"> • Oversized #3 Phillips Flat Wafer Style Head • Modified Buttfress Threads | <ul style="list-style-type: none"> • 2"– 8" (1" Increments) | 2", 3" 4"– 8" | 500 250 |
|  <p>GypTec Fastener</p> | Cementitious Wood Fiber Lightweight Concrete Gypsum | VersiGard, VersiFlex™ and VersiWeld Membranes and Insulation Securement | <ul style="list-style-type: none"> • ¼" Square Drive • Glass-Filled Nylon Fastener | <ul style="list-style-type: none"> • 2½"– 10" (½" Increments) | 2½"– 7½" 8"– 10" | 500 250 |
| | | <p>GypTec Plate (not shown) 1000/ctn 2" Steel Plate for Insulation Attachment 3" Steel Plate for Membrane Attachment</p> | | | | |



FASTENERS & PLATES

| PRODUCT | DECK TYPE | USAGE | DESCRIPTION | SIZE | PACKAGING | |
|---|--|--|---|--|-----------|-----------|
| | | | | | SIZE | # PER CTN |
| MP 14-10 Fastener  | Structural Concrete Steel CDX Plywood Wood Plank | VersiGard, VersiFlex, VersiWeld Membrane Securement Over Wood & Concrete Decks, Insulation Securement Over Steel Decks | <ul style="list-style-type: none"> • #3 Phillips • Truss Head | <ul style="list-style-type: none"> • 2"- 12" (1" Increments) • 14"- 24" (2" Increments) | 2"- 4" | 1000 |
| | | | | | 5"- 11" | 500 |
| | | | | | 12"- 24" | 250 |
| HP Lite Deck Fasteners  | Cementitious Wood Fiber Lightweight Concrete Gypsum | VersiGard and VersiWeld Membranes Insulation Only | <ul style="list-style-type: none"> • Threaded Oversize Diameter Fastener with #3 Square Drive | <ul style="list-style-type: none"> • 2⁵/₈", 3", 4" • 5"- 8" (1" Increments) • 9"- 12" (1" Increments) | | 500 |
| | | | | | | 250 |
| | | | | | | 125 |
| HPVX Fastener  | Steel (20 or 22 gauge) Wood Decks | VersiWeld and VersiFlex Membranes | <ul style="list-style-type: none"> • #3 Phillips • Truss Head • Buttress Threads • Mini-Drill Point | <ul style="list-style-type: none"> • 2"- 12" (1" Increments) • 12"- 14" (2" Increments) | 2"- 4" | 1000 |
| | | | | | 5"- 12" | 500 |
| | | | | | 14" | 250 |
| HPV-XL Fastener  | Steel (22 gauge min) | VersiWeld and VersiFlex Membranes | <ul style="list-style-type: none"> • #3 Phillips Oversized Truss Head • Buttress Threads • Mini-Drill Point | <ul style="list-style-type: none"> • 2"- 8" (1" Increments) | 2"- 6" | 500 |
| | | | | | 7", 8" | 250 |
| CD 10 Nail-In Fastener  | Concrete Decks | VersiGard, VersiFlex and VersiWeld Membranes and Insulation Securement | <ul style="list-style-type: none"> • Hammer Driven • Compression Type Fastener • Diamond Point For Easy Installation | <ul style="list-style-type: none"> • 2"- 6" (½" Increments) • 7"- 12" (1" Increments) | 2"-8" | 500 |
| | | | | | 9"-12" | 250 |






SYSTEM ACCESSORIES

| PRODUCT | DECK TYPE | USAGE | DESCRIPTION | SIZE | PACKAGING | |
|--|--|---|--|---|---|---|
| | | | | | SIZE | # PER CTN |
| Purlin Fasteners  | Structural Steel Purlin (12 gauge max.) | VersiGard, VersiFlex and VersiWeld Metal Retrofit Membrane Securement | <ul style="list-style-type: none"> • ¼" Hex Head • Elongated Self-Drilling Point • Use with HPVX or Insulation Fastening Plates | <ul style="list-style-type: none"> • 3" – 5" (1" Increments) • 6¼", 7¼" | 3" – 7¼" | 500 |
| Zinc Nail-In Anchors  | Concrete Brick Block Walls | VersiGard, VersiFlex and VersiWeld Membranes and Insulation Securement | <ul style="list-style-type: none"> • Zinc Plated Steel Pin with a Zinc Alloy Outer Body | <ul style="list-style-type: none"> • 1¼" x ¼" | | 1000 |
| InsulTite ASAP  | Steel (22 gauge & heavier), Wood Decks | Insulation Only | <ul style="list-style-type: none"> • #3 Phillips Head • Buttfress Threads • Insultite Fastener • Pre-Assembled with Plastic Insulation Plate | <ul style="list-style-type: none"> • 2¼", 2⅝", 3¼", 3¾", 4½" | <ul style="list-style-type: none"> • 2¼"– 8" • 9"– 12" | <ul style="list-style-type: none"> • 250 • 200 |
| HPV ASAP  | Steel (22 gauge & heavier), Wood Decks | VersiGard Membrane Securement | <ul style="list-style-type: none"> • #3 Square Drive • Wafer Style Head • Buttfress Threads • Mini Drill Point • Pre-assembled HPV Fastener with Polymer Seam Plate | <ul style="list-style-type: none"> • 2¼"– 4¼" (½" Increments) • 5"– 12" (1" Increments) • Longer Fastener Sizes Available As Special Order | <ul style="list-style-type: none"> • 2¼", 2¾", 3¼", 3¾" • 4¼", 5" • 6" • 7", 8" • 9" • 10"– 12" | <ul style="list-style-type: none"> • 500 • 450 • 400 • 350 • 300 • 250 • 200 |
| HPVX ASAP  | Steel (20 or 22 gauge) Wood Decks | VersiWeld and VersiFlex Membranes | <ul style="list-style-type: none"> • #3 Phillips Truss Head • Buttfress Threads • Mini-Drill Point • Pre-Assembled with HPVX Plate | <ul style="list-style-type: none"> • 2"– 10" (1" Increments) • 12"– 14" (2" Increments) | <ul style="list-style-type: none"> • 2"– 9" • 10"– 12" • 14" | <ul style="list-style-type: none"> • 250 • 200 • 150 |



FASTENERS & PLATES

SYSTEM ACCESSORIES

| PRODUCT | USED WITH | USAGE | DESCRIPTION | SIZE | PACKAGING |
|--|-------------------------------|---|---|---------------------|-----------|
| | | | | | # PER CTN |
| HPVX-Plate  | HPVX Fastener | VersiWeld and VersiFlex Membranes, Steel, Concrete, Wood | <ul style="list-style-type: none"> 20 Gauge Metal Plate with Reinforcing Ribs and 12 "Gripping Teeth" | • 2 3/8" (Diameter) | 1000 |
| HPV-XL Plate  | HPV-XL Fastener | VersiWeld and VersiFlex Membranes, Steel | <ul style="list-style-type: none"> 20 Gauge Metal Plate with Reinforcing Ribs and 12 "Gripping Teeth" Oversized Hole to Accommodate HPV-XL Fastener | • 2 3/8" (Diameter) | 1000 |
| Polymer Seam Plate  | HPV Fastener | VersiGard Membrane Mechanically-Attached Systems, RTS Attachment | <ul style="list-style-type: none"> Round Nylon Plate with 16 Barb Profile on Underside | • 2" (Diameter) | 1000 |
| Seam Fastening Plate  | HPV Fastener MP14-10, CD-10 | VersiGard Membranes Mechanically-Attached Systems, (Excluding Steel Decks), RTS Attachment (Excluding Mechanically-Attached Systems Over Steel Decks) | <ul style="list-style-type: none"> 20 Gauge, Round Metal Plate with Aluminized Coating | • 2" (Diameter) | 1000 |
| Insulation Fastening Plate  | Insul-Tite MP14-10, CD-10 HPV | Insulation Only on Steel, Wood and Concrete Decks | <ul style="list-style-type: none"> 26 Gauge Round Metal Plate with Aluminized Coating | • 3" | 1000 |

