



VERSICO (BLACK OR WHITE) QUICK APPLIED UNCURD EPDM FLASHING

V-150 PRIMER

NOTES:

1. 180° F (82° C) MAXIMUM TEMPERATURE.
 2. SHAPE METAL DAM TO FIT EXISTING PITCH POCKET.
 3. METAL DAM EXTENSION TO BE 1" (25 mm) MINIMUM FROM PENETRATION ON ANY SIDE.
 4. POURABLE SEALER MUST CONTACT PRIMED QUICK APPLIED UNCURD EPDM FLASHING AND DECK MEMBRANE.
 5. POURABLE SEALER MUST COMPLETELY FILL POURABLE SEALER POCKET TO PREVENT PONDING OF WATER.
 6. POURABLE SEALER TO BE MINIMUM 2" (50 mm) DEEP.
 7. ALL DEBRIS (PAINT, LEAD, OTHER FLASHINGS, ETC.) MUST BE REMOVED FROM THE PENETRATION.
 8. ON MECHANICALLY ATTACHED ROOFING SYSTEMS, ADDITIONAL MEMBRANE SECUREMENT IS REQUIRED. REFER TO SPECIFICATIONS.
- PENETRATIONS, MEMBRANE, FLASHING AND METAL (INSIDE POCKET) MUST BE PRIMED PRIOR TO APPLYING POURABLE SEALER.**

C-16.4

EXTENDED POURABLE SEALER POCKET

