

# Material Safety Data Sheet

G-500CM WATER CUT-OFF MASTIC

MSDS No. 302202

Date of Preparation: 09/15/08

Revision: 022

## Section 1 - Chemical Product and Company Identification

**Product/Chemical Name:** G-500CM WATER CUT-OFF MASTIC

**Chemical Formula:** Mixture

**General Use:** Elastomeric Sealer

**Manufacturer:** Versico, LLC, 1285 Ritner Highway, Carlisle, PA 17013, Phone: 800-992-7663

24 hour Emergency Phone Number: CHEMTREC (USA) 800-424-9300

## Section 2 - Hazards Identification

### ☆☆☆☆☆ Emergency Overview ☆☆☆☆☆

Danger – Highly flammable liquid and vapor

Warning – Causes skin irritation

Warning – Causes eye irritation

Warning – May be harmful if swallowed and enters airways

Warning – May cause an allergic skin reaction

Warning – May cause drowsiness and dizziness

### Potential Health Effects

**Primary Entry Routes:** Skin contact, skin absorption, eye contact, inhalation, ingestion.

**Target Organs:**

**Acute Effects**

**Inhalation:** nose and throat irritation on short-term exposure to liquid or vapor.

**Eye:** irritation on short-term exposure to liquid or vapor

**Skin:** irritation on short-term exposure to liquid or vapor

**Ingestion:** irritation of gastrointestinal tract

**Carcinogenicity:** IARC, NTP, and OSHA do not list this product as a carcinogen.

**Medical Conditions Aggravated by Long-Term Exposure:** Pre-existing eye, skin, and pulmonary disorders may be aggravated by exposure to this product. Respiratory symptoms associated with pre-existing lung disorders and pre-existing heart disorders may be aggravated by exposure to this material.

**Chronic Effects:** Overexposure may result in headache, dizziness, fatigue, nausea, convulsions, and loss of consciousness.

Anorexia and nervousness may persist for several months following acute overexposure. Moderate irritation of skin, eyes, and mucous membranes of upper respiratory tract on prolonged, repeated contact. Dermatitis and defatting of the skin. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage.

**HMIS**

**H** 1

**F** 4

**R** 0

**PPE**†

†Sec. 8

## Section 3 – Ingredient Information

Hazardous Ingredients	CAS Number	% wt
Aliphatic Petroleum Distillate	64742-89-8	10-30
Amorphous Silica	7631-86-9	1-5
Additional Ingredients	CAS Number	% wt
Isobutylene-Isoprene Copolymer	9010-85-9	
Polybutene Homopolymer	9003-29-6	
Hydrous Clay	12174-11-7	
Paraffinic Oil	64742-01-4	
Calcium Carbonate	1317-65-3	

## Section 4 - First Aid Measures

**Inhalation:** Remove victim to fresh air and provide oxygen if breathing is difficult. Give artificial respiration if not breathing. Get medical attention immediately.

**Eye Contact:** Immediately flush eyes with running water for at least 15 minutes. Get medical attention.

**Skin Contact:** Immediately flush skin with running water and remove contaminated clothing. Wash exposed area with soap and water. Get medical attention.

**Ingestion:** Do not induce vomiting. Get medical attention immediately.

**Special Precautions/Procedures:** Whenever possible, remove the worker from the source of contamination.

## Section 5 - Fire-Fighting Measures

**Flash Point:** 40 °F (4 °C)  
**Flash Point Method:** TCC  
**Autoignition Temperature:** 480.4 °F (249 °C)  
**LEL:** 0.9% v/v  
**UEL:** 7% v/v



**Flammability Classification:** Division 2. Ignition can occur when this product is exposed to heat, sparks, or flame.

**Extinguishing Media:** In case of fire, use dry chemical, carbon dioxide, or foam. Water may not be effective as an extinguishing agent. Water fog or spray may be used to provide a smothering effect on fire and to cool fire-exposed container and surrounding combustibles. Do not use a solid stream of water because it can scatter and spread the fire.

**Unusual Fire or Explosion Hazards:** Flammable. Store and use away from all sources of heat, flame, or sparks. DO NOT smoke while applying. Vapors are heavier than air and may travel along ground or may be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking, electrical motors, static discharge, or other ignition sources at location distant from material handling point and flash back. All containers should be grounded when material is transferred.

**Hazardous Combustion Products:** Toxic gases or vapors, such as carbon monoxide, carbon dioxide, or aldehydes may be released in a fire.

**Fire-Fighting Instructions:** This product contains solvents that are dangerous fire and explosion hazards when exposed to heat or flame. Fire fighters should wear self-contained breathing apparatus and full protective clothing with full-face pieces operated in the positive pressure demand mode.

**Fire-Fighting Equipment:** Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

## Section 6 - Accidental Release Measures

**Spill /Leak Procedures:** Remove all sources of ignition. Avoid breathing vapors. Use self-contained breathing apparatus in enclosed area. Ventilate area. Contain and remove with inert absorbent materials and non-sparking tools.

### Large Spills

**Containment:** For large spills, dike far ahead of liquid spill for later disposal. Do not release into sewers or waterways.

**Cleanup:** Clean-up spill as soon as possible. Collect any excess material with absorbent pads, sand, or other inert non-combustible absorbent materials. Place into appropriate waste containers for later disposal. Comply with all laws and regulations.

**Regulatory Requirements:** Follow applicable OSHA regulations (29 CFR 1910.120).

## Section 7 - Handling and Storage

**Handling Precautions:** Use away from all sources of heat, flame, or sparks. Do not smoke while using. Handling equipment must be grounded to prevent sparking. Handle with non-sparking tools. Wash with soap and water before eating or drinking. Launder contaminated clothing. KEEP OUT OF REACH OF CHILDREN.

**Storage Requirements:** Keep containers cool, dry, and store away from all sources of heat, flame, and sparks. Keep containers tightly closed and store with adequate ventilation. Do not pressurize, cut, weld, or grind the containers or empty containers which may contain residual product and solvent vapors that may ignite explosively.

## Section 8 - Exposure Controls / Personal Protection

### Hazardous Ingredients:

Ingredient	OSHA PEL		ACGIH TLV		NIOSH REL		NIOSH IDLH
	TWA	STEL	TWA	STEL	TWA	STEL	
Aliphatic Petroleum Distillate	300 ppm	400 ppm	300 ppm	none estab.	350 ppm	none estab.	none estab.
Amorphous Silica	6.0mg/m <sup>3</sup> (total dust)	none estab.	none estab.	none estab.	none estab.	none estab.	none estab.

**Engineering Controls:** Do not use in enclosed areas without proper explosion-proof ventilation. General and local exhaust ventilation must be sufficient to control vapor concentrations and keep the vapor concentration below 300 ppm.

**Ventilation:** Provide general or local exhaust ventilation systems to maintain airborne concentrations below OSHA PELs. Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

**Respiratory Protection:** A NIOSH approved respirator must be used if vapor concentration is 300 ppm or above.

**Protective Clothing/Equipment:** Permeation resistant gloves (that meet ANSI/ISEA 105-2005) recommended. Glasses or goggles recommended. Wear industrial boots to protect feet from contact with sealant. Impervious clothing is recommended to protect skin from contact with sealant. Protective skin creams or emollients useful.

**Safety Stations:** Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.

**Contaminated Equipment:** Separate contaminated work clothes from street clothes. Launder before reuse. Remove this material from your shoes and clean personal protective equipment.

**Comments:** Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.

## Section 9 - Physical and Chemical Properties

**Physical State:** Liquid

**Appearance and Odor:** Gray viscous liquid with mild solvent odor

**Odor Threshold(ppm):** Not available

**Vapor Pressure:** 45 mm Hg at 25 °C(77°F)

**Vapor Density (Air=1):** 3.9

**Density:** 9.98 – 10.82 lbs./gal. (calculated)

**Specific Gravity (H<sub>2</sub>O=1, at 4°C/39°F):** 1.20-1.30

**pH:** N/A

**Water Solubility:** 0.5

**Other Solubilities:**

**Boiling Point(°C):** 115-140 (239 - 284°F)

**Freezing/Melting Point(°C):** -18 (-0.4°F)

**% Volatile:** 10-20

**Evaporation Rate:** 2.0

**VOC:** 250 gms. /l.

**Flash Point:** 40 °F (4 °C)

**Flash Point Method:** TCC

**Autoignition Temperature:** 480.4 °F (249 °C)

**LEL:** 0.9% v/v

**UEL:** 7% v/v

## Section 10 - Stability and Reactivity

**Stability:** Stable.

**Possibility of hazardous reactions:** Will not occur.

**Chemical Incompatibilities:** Strong oxidizing agents, acids, bases.

**Conditions to Avoid:** Heat, sparks, and flames; ignition sources.

**Hazardous Decomposition Products:** Toxic gases or vapors such as carbon monoxide, carbon dioxide, or aldehydes may be released in a fire.

## Section 11- Toxicological Information

### Toxicity Data:

**Acute Inhalation Effects:** Product toxicity has not been determined.

**Acute Oral Effects:** Product toxicity has not been determined.

The following is component data:

Aliphatic Petroleum Distillates - Rat, oral, LD<sub>50</sub>: >5000mg/kg

Amorphous Silica - Rat, oral, LD<sub>50</sub>: 3160mg/kg

**Carcinogenicity:** Not listed in IARC or NTP.

**Mutagenicity:** No evidence

**Teratogenicity:** No evidence

## Section 12 - Ecological Information

This product has not been tested. No data available.

## Section 13 - Disposal Considerations

**Disposal:** Dispose of in accordance with all local, state, and federal regulations.

## Section 14 - Transport Information

### DOT Transportation Data (49 CFR 172.101):

**Shipping Name:** Adhesives

**Shipping Symbols:** Flammable

**Hazard Class:** 3

**ID No.:** UN1133

**Packing Group:** II

**Label:** flammable liquid label  
required for 5 gallon pails only

**Special Provisions (172.102):**  
149,B52,IB2

### Packaging Authorizations

a) **Exceptions:** 173.150

b) **Non-bulk Packaging:** 173.173

c) **Bulk Packaging:** 173.242

### Quantity Limitations

a) **Passenger, Aircraft, or Railcar:** 5 L

b) **Cargo Aircraft Only:** 60 L

### Vessel Stowage Requirements

a) **Vessel Stowage:** B

b) **Other:** N/A

**Section 15 - Regulatory Information****EPA Regulations:**

RCRA Hazardous Waste Number: Not listed (40 CFR 261.33)

RCRA Hazardous Waste Classification (40 CFR 261.31): Not classified

CERCLA Hazardous Substance (40 CFR 302.4) listed/unlisted specific per RCRA, Sec. 3001; CWA, Sec. 311 (b)(4); CWA, Sec. 307(a), CAA, Sec. 112: Not listed

SARA 311/312 Codes:

SARA Toxic Chemical (40 CFR 372.65): Not listed

SARA EHS (Extremely Hazardous Substance) (40 CFR 355): Not listed

**OSHA Regulations:**

Air Contaminant (29 CFR 1910.1000, Table Z-1, Z-1-A): Not listed

**State Regulations:**

Massachusetts Hazardous Substance Codes: Amorphous Silica 7631-86-9 2,4,5,F5  
Calcium Carbonate 1317-65-3 4

Minnesota Hazardous Substance: Amorphous Silica Codes: ANOR Carcinogen: Yes  
Calcium Carbonate Codes: A Carcinogen: No

Pennsylvania Hazardous Substance Code: Amorphous Silica 7631-86-9 Code: None  
Calcium Carbonate 1317-65-3 Code: None

**Canadian WHMIS Classification:** Class: B  
Division 2

**Section 16 - Other Information**

**Prepared By:** Research & Development

**Revision Notes:** General Revision – Format Changes

**Disclaimer:** The information contained in this document is based upon data that was supplied to Versico by other companies and organizations. No warranty of merchantability or fitness for a particular purpose is expressed or implied regarding the accuracy or completeness of the data and/or information in this material safety data sheet.