

VERSICO ASAP INSULTITE INSULATION FASTENERS

GENERAL:



The Versico ASAP Insul-Tite Insulation Fastener consists of a 3-inch round plastic locking insulation plate and a threaded #12 fastener pre-assembled as one unit. Used for insulation attachment on VersiGard® and VersiWeld® mechanically attached and fully adhered roofing systems, the ASAP greatly reduces installation time when compared to loose fasteners and plates. The Versico ASAP Insulation Fastener is used to attach insulation to wood (minimum 15/32" [12mm] CDX plywood) or steel decks (22 gauge [.076 mm] or heavier).

TYPICAL PROPERTIES AND CHARACTERISTICS:

Size, in	Thread Length, in	Weight/Carton, lb	Fasteners/Carton
2 ¼	Full	11	250
2 7/8	Full	12	250
3 1/4	3	13	250
3 ¾	3	14	250
4 ½	3	16	250
5	3	18	250
6	4	19	250
7	4	20	250
8	4	22	250

1. The fastener is manufactured from #12 wire and incorporates #3 Phillips drive.
2. The coatings used on the fastener and plate provide excellent corrosion resistance, surpassing the FM 4470 requirements of less than 15% red rust after 15 cycles in the Kesternich cabinet
3. One Phillips driver bit is provided in each box of fasteners.

CAUTIONS AND WARNINGS:

- Eye protection is recommended during drilling and installation.
- Use care to avoid over-torquing the fastener

INSTALLATION:

- Place the Versico ASAP fastener and plate at the desired location and install with a standard clutch drive electric screw gun. No pre-drilling is necessary for wood and steel (18 gauge or less) decks since the fastener is self-drilling. The minimum penetration depth (measured from the top surface) is 1-inch for wood and $\frac{3}{4}$ inch for steel.