


## VERSICO CD-10 CONCRETE FASTENER

### GENERAL:



The CD-10 is a heavy-duty threaded fastener designed to be used with Versico's various fastening plates to secure mechanically attached membranes, insulation and RTS into structural concrete (minimum 2500 psi) roof decks. The CD-10 Fastener also features outstanding pullout and corrosion resistance.

### TYPICAL PROPERTIES AND CHARACTERISTICS:

Size, inches (mm)	Weight/Carton, lb. (kg)	Fasteners/Carton
2 (50)	13 (5.9)	500
2-1/2 (63)	16 (7.3)	500
3 (75)	18 (8.2)	500
3-1/2 (88)	21 (9.5)	500
4 (100)	23 (10.4)	500
4-1/2 (115)	25 (11.4)	500
5 (127)	28 (12.7)	500
5-1/2 (140)	31 (14.0)	500
6 (150)	33 (15.0)	500
7 (175)	38 (17.3)	500
8 (200)	44 (20.0)	500
9 (225)	25 (11.4)	250
10 (250)	28 (12.7)	250
11 (280)	31 (14.0)	250
12 (300)	33 (15.0)	250

1. The epoxy electro-deposition coating provides excellent corrosion resistance, surpassing the FM 4470 corrosion test of less than 15% red rust after 15 cycles in the Kesternich cabinet.

### CAUTIONS AND WARNINGS:

- The pilot hole must be pre-drilled to a sufficient depth to prevent contact between the fastener tip and any accumulated dust in the pre-drilled hole.
- Eye protection is recommended during drilling and installation.

**INSTALLATION:**

Drill a hole with an ANSI standard 7/32" diameter drill bit. Insert the fastener through the appropriate plate and secure with a hammer. Minimum embedment depth is 1".