


VERSICO MP 14-10 CONCRETE FASTENER

GENERAL:



The MP 14-10 is a heavy-duty threaded fastener designed to be used with Versico's various fastening plates to secure mechanically fastened membranes, insulation and Reinforced Termination Strips into structural concrete (minimum 2500 psi) roof decks. The MP 14-10 Fastener also features outstanding pullout and corrosion resistance.

TYPICAL PROPERTIES AND CHARACTERISTICS:

Size, in (mm)	Weight / Carton, lb (kg)	Fasteners / Carton
2 (50)	18 (8.2)	1000
3 (76)	26 (11.8)	1000
4 (102)	34 (15.4)	1000
5 (127)	21 (9.5)	500
6 (152)	25 (11.3)	500
7 (178)	29 (13.2)	500
8 (203)	33 (15.0)	500
9 (229)	36 (16.3)	500
10 (254)	40 (18.1)	500
11 (279)	44 (20.0)	500
12 (305)	49 (22.2)	500

1. The fastener is manufactured from # 14 wire and incorporates a # 3 Phillips drive.
2. The epoxy electro-deposition coating provides excellent corrosion resistance, surpassing the FM 4470 corrosion test of less than 15% red rust after 15 cycles in the Kesternich cabinet.

CAUTIONS AND WARNINGS:

1. The pilot hole must be pre-drilled to a sufficient depth to prevent contact between the fastener tip and any accumulated dust in the pre-drilled hole.
2. Eye protection is recommended during drilling and installation.
3. High strength concrete decks can cause threaded fasteners to break (twist off) during installation. Use the Versico CD-10 concrete spike if fastener breakage is persistent.

INSTALLATION:

Drill a hole with an ANSI standard 3/16 inch (5 mm) diameter drill bit. A 7/32 inch (5.6 mm) diameter bit may be substituted for the 3/16 inch bit if fastener breakage is encountered. Check to be sure that the pullout resistance has not been compromised when using the 7/32 inch bit. Insert the fastener through the appropriate plate and tighten with a screw gun. The minimum embedment depth is 1 inch (25.4 mm).