


## VERSICO INSULTITE INSULATION FASTENERS

### GENERAL:



The Versico Insultite Fastener is used in conjunction with a Versico 3" Insulation Plate for insulation attachment on VersiGard<sup>®</sup>, White VersiGard and VersiWeld<sup>®</sup> Mechanically-Attached and Fully Adhered roofing systems. Available in lengths from 1 5/8" to 8", the Insultite Insulation Fastener features a buttress thread design for high pullout resistance and an extra sharp spade point for quick installation. It is designed to secure insulation to wood (minimum 15/32" (12 mm) CDX plywood) or steel decks (22 gauge (0.76 mm) or heavier).

### TYPICAL PROPERTIES AND CHARACTERISTICS:

Size, in (mm)	Thread Length, in (mm)	Weight/Carton, lb.	Fasteners/Carton
1-5/8 (41)	Full	12 (5.4)	1,000
2-1/4 (57)	Full	16 (7.3)	1,000
2-7/8 (73)	Full	19 (8.6)	1,000
3-1/4 (83)	3 (76)	22 (10.0)	1,000
3-3/4 (95)	3 (76)	25 (11.4)	1,000
4-1/2 (114)	3 (76)	29 (13.2)	1,000
5 (127)	3 (76)	35 (15.9)	1,000
6 (152)	4 (102)	42 (19.1)	1,000
7 (178)	4 (102)	48 (21.8)	1,000
8 (203)	4 (102)	55 (25.0)	1,000

1. The fastener incorporates a #3 Phillips drive.
2. The coating used on the fastener provides excellent corrosion resistance, surpassing the FM 4470 requirements of less than 15% red rust after 15 cycles in the Kesternich cabinet.
3. One Phillips driver bit is provided in each box of fasteners.

### CAUTIONS AND WARNINGS:

1. Eye protection is recommended during installation.

2. Use care to avoid over-torquing the fastener. Fastener must be tight enough so that the plate doesn't turn.

### **INSTALLATION:**

Place the Insultite Fastener and Versico Insulation Plate at the desired location and install with a standard clutch drive screw gun. No pre-drilling is necessary for wood and steel (18 gauge or less) decks since the fastener is self-drilling. The minimum penetration depth (measured from the top surface) is 1-inch (25 mm) for wood and ¾ inch (19 mm) for steel.