

VERSICO VERSIWELDä CUT-EDGE SEALANT

GENERAL:

Versiweld Cut-Edge Sealant is designed to seal cut edges of Versiweld reinforced membrane. This sealant is available as a medium solids content, free-flowing, polymeric sealant packaged in 16 ounce squeeze bottles.

TYPICAL PROPERTIES AND CHARACTERISTICS: *

Base	Synthetic Rubber
Color	White, Gray, Tan
Solids	25%
Viscosity	2,000 cps
Flash Point	81°F
Net Weight Gallon	7.8 lbs.
Resistance to:	
Ozone	Excellent
UV	Excellent
Water	Excellent
VOC	700 grams per liter
Packaging	Eight 16 oz. Bottles/Carton
Shelf Life	1 Year

CAUTIONS AND WARNINGS:

1. Review the applicable Material Safety Data Sheet for complete safety information.
2. Cut-Edge Sealant is **FLAMMABLE** -- It contains solvents that are dangerous fire and explosion hazards when exposed to heat, flame or sparks. Do not smoke while applying. Do not use in a confined or unventilated area. Vapors are heavier than air and may travel along the ground to a distant ignition source and flashback.
3. Avoid breathing vapors. Keep container closed when not in use. Use with adequate ventilation. If inhaled, remove to fresh air. If not breathing, perform artificial respiration. If breathing is difficult, give oxygen. Call a physician immediately.
4. If swallowed, **DO NOT INDUCE VOMITING**. Call a physician immediately.
5. Avoid contact with eyes. Safety glasses or goggles are recommended. If splashed in eyes, immediately flush eyes with plenty of water for at least 15 minutes. Contact a physician immediately.

6. Avoid contact with skin. Wash thoroughly after handling. In case of contact with skin, thoroughly wash affected area with soap and water.
7. Job site storage temperatures in excess of 90°F may affect product shelf life. Should the Cut-Edge Sealant be stored at temperatures below 60°F, restore to room temperature prior to use.
8. **KEEP OUT OF THE REACH OF CHILDREN.**

COVERAGE:

Approximately 250 ft per bottle when applied with 1/8" bead.

APPLICATION:

1. All surfaces to be sealed with Cut-Edge Sealant must be clean, dry and free from oil, grease, dirt and other foreign materials.
2. Apply a 1/8" bead of Cut-Edge Sealant to seal cut edges of reinforced Versiweld Premier Membrane. Do not apply Cut-Edge Sealant on vertical surfaces.

* General properties. Typical properties and characteristics are based on samples tested and are not guaranteed for all samples of this product. This data and information is intended as a guide and does not reflect the specification range for any particular property of this product.