

VERSIWELDä PENETRATION POCKETS

GENERAL:

Versiweld Penetration Pockets are a prefabricated pocket consisting of a 2" wide plastic support ring with pre-applied Versiweld Flashing (Patent #4,928,443). Versiweld Penetration Pockets are ideal for sealing irregular, hard to flash penetrations through the membrane.

TYPICAL PROPERTIES AND CHARACTERISTICS:

Sizes:	6" and 8" Diameter
Packaging:	2 Pockets/Carton
Weight:	2 lbs./carton
Color:	White, Gray, Tan

CAUTIONS AND WARNINGS:

1. Temperature of penetration shall not exceed 180°F.
2. CCW-102 Sealant must completely fill sealant pocket and must be crowned 1/2" to prevent ponding water. Penetrations must be clean before filling with sealant.
3. Sealant pockets to be one inch minimum from penetration on any side.
4. UV filtering sunglasses are strongly recommended when working on Versiweld Roofing Systems.
5. Store sealant pockets in a cool, shaded area and cover with light-colored, breathable, waterproof tarpaulins. Versiweld pockets or membrane that have been exposed to the weather for approximately 7 days or longer prior to use must be prepared with Versico Weathered Membrane Cleaner prior to hot air welding.

INSTALLATION:

1. See appropriate installation guide.