

Safety Data Sheet

Material Name: X-Tenda Coat Bleed Block Primer

Product #: 340582 – Drum
340583 - Pail

Section 1 - PRODUCT AND COMPANY IDENTIFICATION

Material Name

X-Tenda Coat Bleed Block Primer

Product Use

Roof primer

Restrictions on Use

For industrial use only.

Manufacturer Information

Versico
1285 Ritner Highway
Carlisle, PA 17013
USA
Phone: +1-800-992-7663
Emergency Phone #: +1-800-424-9300 (CHEMTREC)

Section 2 - HAZARDS IDENTIFICATION

GHS Ratings:

Skin sensitizer – Category 1 Skin sensitizer

GHS Hazards

H317 May cause an allergic skin reaction

GHS Precautions

P261	Avoid breathing dust/fume/gas/mist/vapors/spray
P272	Contaminated work clothing should not be allowed out of the workplace
P280	Wear protective gloves/protective clothing/eye protection/face protection
P321	Specific treatment is urgent (see Section 4 First Aid measures)
P363	Wash contaminated clothing before reuse
P302+P352	IF ON SKIN: Wash with soap and water
P333+P313	If skin irritation or a rash occurs: Get medical advice/attention
P501	Dispose of contents/container in accordance with existing federal, state, and local environmental control laws.

Signal Word: Danger



Acute Toxicity:

Eyes: May cause irritation & burns.

Skin: Minor potential for irritation.



Safety Data Sheet

Material Name: X-Tenda Coat Bleed Block Primer

Product #: 340582 – Drum
340583 - Pail

Inhalation: Liquid may cause irritation.

Ingestion: Consult physician.

Conditions Aggravated: None known.

Chronic Effects: Not expected to cause any adverse chronic health effects.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component Name	Percent
1317-65-3	Limestone	50.00% - 60.00%
25068-38-6	Bisphenol A-epichlorohydrin polymer	40.00% - 50.00%
13463-67-7	Titanium dioxide	1.00% - 5.00%
75-21-8	Ethylene Oxide	0.10% - 1.00%
123-91-1	1,4-Dioxane	0.10% - 1.00%
	Acetaldehyde	0.10% - 1.00%

Section 4 - FIRST AID MEASURES

After Inhalation: If symptoms ensue, move to fresh air. If breathing is difficult, give oxygen.

After Eye Contact: Rinse opened eye for at least 15 minutes under running water.

Remove contact lenses if present and easy to do so, and continue rinsing.

After Skin Contact: Clean affected area with soap and plenty of water.

After Swallowing: Consult physician.

Notes to Physician: Treat symptomatically.

Section 5 – FIRE FIGHTING MEASURES

Flash Point: 122°C (252°F)

LEL: N/A

UEL: N/A

Upper and lower explosive limits listed if known.

Suitable Extinguishing Agents: Water spray, CO₂, Foam, Dry chemical

Information about Protection against Explosions and Fires: Closed containers may rupture when exposed to extreme heat.

Dangerous Products of Decomposition: Oxides of carbon, oxides of nitrogen, and traces of HCN.



Safety Data Sheet

Material Name: X-Tenda Coat Bleed Block Primer

Product #: 340582 – Drum
340583 - Pail

Protective Equipment: Firefighters should wear a pressure demand self-contained breathing apparatus and protective clothing.

Section 6 - ACCIDENTAL RELEASE MEASURES

Person-Related Safety Precautions: Avoid contact with skin and eyes. Do not breathe vapors.

Measures for Environmental Precaution: Cover and contain spill with absorbent material. Collect for proper disposal according to local, state, and federal regulations.
Clean up with water. Avoid discharge into drains, water courses, or onto the ground.

Section 7 - HANDLING AND STORAGE

Information for Safe Handling: Avoid contact with skin or inhalation.

Storage Requirements: Store in dry, well ventilated area. Keep containers tightly closed, Store between 45°F-100°F. Material may freeze below 32°F. Material may settle.

Regulatory Requirements: Store according to all local, state, and federal regulations.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Talc	14807-96-6
OSHA:	Not Established
ACGIH:	2 mg/m ³ TWA (particulate matter containing no asbestos and <1% crystalline silica, respirable fraction)
Other:	NIOSH: 2 mg/m ³ TWA (containing no Asbestos and <1% Quartz, respirable dust)
Mica	12001-26-2
OSHA:	2 mg/m ³ (respirable dust)
ACGIH:	2 mg/m ³ TWA (respirable dust)
Other:	Not Established
Diethoxy(3-glycidyoxypropyl) methylsilane	2897-60-1
OSHA:	Not Established
ACGIH:	Not Established



Safety Data Sheet

Material Name: X-Tenda Coat Bleed Block Primer

Product #: 340582 – Drum
340583 - Pail

Other:	Not Established
--------	-----------------

Engineering Controls: No specific measures required if proper PPE precautions are followed.

Ventilation: Good general ventilation (typically 10 air changes per hour) should be used, Ventilation rates should be matched to conditions.

General Protective and Hygienic Measures: Usual precautionary measures should be adhered to when handling chemicals.

Personal Protective Equipment:

Respiratory Protection: None required if work area is properly ventilated.

Hand Protection: Protective chemical resistant gloves.

Eye Protection: Safety glasses with side shield.

Body Protection: Protective work clothing. Launder separately.

Contaminated Gear: Observe local requirements. Dispose of in accordance with local/state/federal regulations.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical properties listed where known.

Appearance	Light brown/tan liquid	Odor	Mild
Vapor Pressure	N/A	Odor threshold	N/A
Vapor Density	N/A	pH	N/A
Specific Gravity	1.11	Melting point	N/A
Freezing point	N/A	Solubility	N/A
Boiling range	122 – 126°C	Flash point	>212°F, 100°C
Evaporation rate	N/A	Flammability	N/A
Explosive Limit	N/A	Partition coefficient: n-octanol/water	N/A
Autoignition temperature	N/A	Decomposition temperature	N/A

Section 10 - STABILITY AND REACTIVITY

Incompatible Materials: Avoid contact with strong acids, strong bases, and oxidizing agents.

Hazardous Polymerization: Not expected to occur.



Safety Data Sheet

Material Name: X-Tenda Coat Bleed Block Primer

Product #: 340582 – Drum
340583 - Pail

Dangerous Products of Decomposition: Oxides of carbon, oxides of nitrogen, traces of HCN.

Section 11 - TOXICOLOGICAL INFORMATION

Mixture Toxicity
Component Toxicity

Toxicity Values Listed if Known

Acute Toxicity:

Eyes: May cause irritation & burns.

Skin: Minor potential for irritation.

Inhalation: Liquid may cause irritation.

Ingestion: Consult physician.

Chronic Effects: Not expected to cause any adverse chronic health effects.

Routes of Entry: Skin contact.

Target Organs: Skin.

Chemicals with Known or Possible Carcinogenic Effects:

<u>CAS Number</u>	<u>Description</u>	<u>% Weight</u>	<u>Carcinogen Rating</u>
None			None

Section 12 - ECOLOGICAL INFORMATION

General Information: Based on experience, no adverse effects are to be expected if correct disposal procedures have been followed as indicated in section 13.

Component Ecotoxicity

Talc 96 Hr LC50 Brachydanio rerio: >100 g/L [semi-static]

Section 13 - DISPOSAL CONSIDERATIONS

Recommendation: Observe local requirements. Dispose of in accordance with local/state/federal regulations.

Empty Container Precautions: Empty containers retain product residue; observe all precautions for product. Do not heat or cut empty container with electric or gas torch because highly toxic vapors and gases are formed. Do not reuse without thorough commercial cleaning and reconditioning. If container is to be disposed, ensure all product residues are removed and container is empty prior to disposal. Contact the Reusable Industrial Packaging Association (RIPA) at 301-577-3786 to find a drum re-conditioner in North America (www.reusablepackaging.org).



Safety Data Sheet

Material Name: X-Tenda Coat Bleed Block Primer

Product #: 340582 – Drum
340583 - Pail

Section 14 - TRANSPORT INFORMATION

DOT Regulated Components:

This product is not regarded as dangerous good according to the national and international regulations on the transport of dangerous goods unless specifically cited below.

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
	None			

Section 15 - REGULATORY INFORMATION

OSHA HAZARD COMMUNICATION STANDARD: This material is classified as hazardous in accordance with OSHA 29 CFR 1910.1200.

SARA Section 311/312 Hazard Categories: Acute health hazard.

California Proposition 65

(Safe Drinking Water and Toxic Enforcement Act of 1986)

This product contains no substances known to the State of California to cause cancer, birth defects or other reproductive harm, at levels which would require a warning under the statute unless otherwise listed:

WARNING: This product can expose you to chemicals listed below, which are known to the State of California to cause cancer, birth defects, or reproductive harm. For more information, visit

www.P65Warnings.ca.gov

- None

Massachusetts Right To Know List:

Talc 14807-96-6 5 to 10 %

New Jersey Right To Know List:

Diethoxy(3-glycidyloxypropyl)methylsilane 2897-60-1 0.1 to 1.0 %

Talc 14807-96-6 5 to 10 %

Pennsylvania Right To Know List:

Diethoxy(3-glycidyloxypropyl)methylsilane 2897-60-1 0.1 to 1.0 %

Talc 14807-96-6 5 to 10 %

SARA 302 Extremely Hazardous Substances:

- None

Chemicals subject to SARA 313 Reporting:

- None

<u>Country</u>	<u>Regulation</u>	<u>All Components Listed</u>
Canada	Canada DSL	Yes
US	Toxic Substances Control Act	Yes



Safety Data Sheet

Material Name: X-Tenda Coat Bleed Block Primer

Product #: 340582 – Drum
340583 - Pail

Section 16 - OTHER INFORMATION

Summary of Changes

New SDS: July 22, 2020

Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD - Dangerous Substance Directive; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of Lists™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH - Philippines; RCRA - Resource Conservation and Recovery Act; REACH- Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US - United States.

Other Information

Disclaimer:

The information contained herein is based upon data and information available to us, and reflects our best professional judgment. This product may be formulated in part with components purchased from other companies. No warranty of merchantability, fitness for any use, or any other warranty is expressed or implied regarding the accuracy of such data or information. The results to be obtained from the use thereof, or that any such use does not infringe any patent, since the information contained herein may be applied under conditions of use beyond our control and with which we may be unfamiliar, we do not assume responsibility for the results of such application. This information is furnished upon the condition that the person receiving it shall make his own determination of the suitability of the material for his particular use.